



| SRK Length (ft.) | Kit Weight (lb.) |
|------------------|------------------|
| 300 ft.          | 7.4 lbs.         |
| 350 ft.          | 8.1 lbs.         |
| 394 ft.          | 9.3 lbs.         |
| 600 ft.          | 12.3 lbs.        |

## SRK-11<sup>®</sup> (Self-Rescue Kit)

Each worker has his own kit - assuring independent, immediate, and adaptable escape and self-rescue capability! The **SRK-11<sup>®</sup>** is used for the self-rescue of any worker at height. This Kit has been field tested for over a decade and is used in multiple industries globally.

- Tech Safety Lines' unique escape and Self-Rescue Kit, utilizes high heat aramid fiber rope with a tensile strength exceeding 6,700 lbs.
- Vectran rope is specifically designed for strength retention in chemical exposures covering a wide range of aggressive chemicals, concentrations, exposure times, and temperatures.
- The service life of the rope is 10 years.
- The Descender (MCDII) has a dual braking system, both an active brake and a passive brake.
- The SRK-11<sup>®</sup> is certified for distances up to 600 feet (186m).
- The SRK bags have a "no-drop" loop stitched inside which protects against dropping the descender during kit access.
- The SRK bag is fabricated from a cut resistant ballistic fabric.

The **SRK-11<sup>®</sup>** is 3rd party certified by UL as meeting **ANSI Z359.4-2013**.

We also offer the **SRK-15<sup>®</sup>** that is 3rd party certified by TÜV SÜD as being **CE compliant for EN341: 2011/2D**

### The mandatory Z359.4 – 2013 test includes:

- Descent Energy and Capacity
- Static Strength
- Dynamic Strength
- Function and Descent Speed – conducted after wet conditioning in addition to testing after room conditioning.
- Corrosion Resistance (96 hours)
- Static Strength of rope

**Tech Safety Lines, Inc.**  
 3350 Wiley Post Road  
 Carrollton, Texas 75006  
[www.techsafetylines.com](http://www.techsafetylines.com)

#### Questions?

Contact TSL at (214) 987-4680 or  
 e-mail [info@techsafetylines.com](mailto:info@techsafetylines.com)